

Fonte Wall-Mounted Bath Shower Mixer

WALL MOUNTED · FITTING SEQUENCE

CL – BF – 004

IN THE BOX	SUPPLIES	MIN PRESSURE
Backplate assembly · two spouts (240 / 200 mm) · two handles · handset · 1.5 m hose	Hot + cold · G½	0.5 bar

SEQUENCE

- ISOLATE**
Isolate the hot and cold supplies before any work begins.
- SET OUT**
Offer the backplate to the wall with the spout station clear of the bath rim. Mark the fixing positions and the two supply connections — the plate is 350 × 80 mm with its stations at 70 mm centres. Confirm the wall will carry the assembly.
- FIRST FIX**
Bring the hot and cold supplies to the marked connection points, terminating G½ to suit the assembly. Flush the pipework through before connection.
- CHOOSE THE SPOUT**
Two spouts travel in the box — 240 mm and 200 mm. Fit the one that suits the bath to the spout station and seat its seal.
- MOUNT**
Fix the backplate assembly to the wall, make the hot and cold connections, and seal the plate line to the finished wall.
- HANDSET**
Connect the 1.5 m hose to the handset and to the plate outlet, then rest the handset in its holder.
- HANDLE CHOICE**
Both handles travel in the box — one knurled, one smooth. Swap at the control's fixing without disturbing the plumbing.
- COMMISSION**
Open the supplies and check every joint under pressure. Run the mixer to temperature, then run the diverter both ways and check the handset spray.

NOTE

Constructed sequence. Where the supplied manufacturer instruction differs, follow it.