Incasso Flush Pull

ROUND FLUSH PULL · POCKET DOOR · SOLID BRASS · PUSH-FIT

`CL — FP — 001 — [ALL FINISHES]`

MARKING	RECESS	DEPTH	SEATING
Pencil & square	Forstner bit	12.7 mm stop	Soft mallet & block

FITTING SEQUENCE · ONE PULL ON EACH FACE

1 MARK

With the door off the pocket frame, mark the pull centre on each face at hand height, set in from the leading edge so the 57 mm face clears the edge and any lock.

2 RECESS

On each face bore a recess to suit the body below the lip — `check against the part`, `12.7 mm` deep. Use a depth stop so the floor is flat and the depth exact.

3 TEST

Offer the pull to the recess before seating. The body should enter with a firm push and the lip should meet the door face all round.

4 SEAT

Press the pull home with a soft mallet over a timber block until the lip sits down evenly — `0.3 mm` proud, nothing more. No screws or adhesive are needed.

BEFORE YOU START

Fit both pulls before the door goes into the pocket frame. On a privacy door, the Cast Pocket Door Lock supplies its own flush turn and release — use these pulls on passage doors, or as a second pull away from the lock.

CARE

Wipe with a soft, dry cloth. No abrasives, no solvents, no polish. Living finishes will deepen in tone with use — this is intended.

SUPPORT

Technical documents are available on request. Write to studio@castlondon.co.uk quoting the serial on this sheet.

INCASSO · FLUSH PULL · SERIES 02 / HARDWARE · SOLID BRASS · QC PASSED · CL-QC-001