Incasso Flush Pull Long

RECTANGULAR FLUSH PULL · POCKET DOOR · SOLID BRASS · 105 × 44

CL — FP — 002 — [ALL FINISHES]

MARKING	RECESS	DEPTH	FIXING
Pencil, square & knife	Router & chisel	9.5 mm stop	Pin hammer or adhesive

FITTING SEQUENCE · ONE PULL ON EACH FACE

1 MARK

With the door off the pocket frame, mark the pull centre on each face at hand height. Set the long side vertical, clear of the leading edge and any lock.

2 RECESS

Rout a **98 × 37 mm** recess **9.5 mm** deep on each face and square the corners with a chisel. The body should drop in without forcing.

3 FIX

Seat the pull so the face plate lies flat on the door. Fix with the panel pins supplied, or bed it on a thin line of adhesive. Do not overdrive the pins.

4 CHECK

The plate should sit flat with no rock. The dish has no inner lip — it guides the door rather than gripping it; specify it for flat, light-running sliding doors.

BEFORE YOU START

Sold singly — order two for a door that slides from both faces. Fit before the door goes into the pocket frame. On a privacy door, the Cast Pocket Door Lock supplies its own flush turn and release.

CARE

Wipe with a soft, dry cloth. No abrasives, no solvents, no polish. Living finishes will deepen in tone with use — this is intended.

SUPPORT

Technical documents are available on request. Write to studio@castlondon.co.uk quoting the serial on this sheet.

INCASSO FLUSH PULL LONG SERIES 02 / HARDWARE SOLID BRASS QC PASSED · CL-QC-001