Incasso Flush Pull Reeded

ROUND REEDED FLUSH PULL · POCKET DOOR · SOLID BRASS · Ø 63.5

CL — FP — 003 — [ALL FINISHES]

MARKING	RECESS	DEPTH	FIXING
Pencil & square	Ø 54.5 mm Forstner bit	10 mm stop	Clear adhesive

FITTING SEQUENCE · ONE PULL ON EACH FACE

1 **MARK**

With the door off the pocket frame, mark the pull centre on each face at hand height, set in so the 63.5 mm face clears the leading edge and any lock.

2 **RECESS**

On each face bore a **Ø 54.5 mm** recess **10 mm** deep with a depth stop, so the floor is flat and the depth exact.

3 **TEST**

Offer the pull to the recess dry. The body should enter cleanly and the reeded ring should sit down evenly on the door face all round.

4 **FIX**

Apply a thin bead of adhesive to the body, press the pull home with the reeds square to the face, and wipe away any squeeze-out before it sets.

BEFORE YOU START

Sold singly — order two for a door that slides from both faces. Fit before the door goes into the pocket frame. On a privacy door, the Cast Pocket Door Lock supplies its own flush turn and release.

CARE

Wipe with a soft, dry cloth. No abrasives, no solvents, no polish. Living finishes will deepen in tone with use — this is intended.

SUPPORT

Technical documents are available on request. Write to studio@castlondon.co.uk quoting the serial on this sheet.

INCASSO FLUSH PULL REEDED SERIES 02 / HARDWARE SOLID BRASS QC PASSED · CL-QC-001